



FREEZETECH İÇ VE DIŞ TİCARET LİMİTED ŞİRKETİ

www.freezetechtrade.com

Freezetech

As Freeztech team, we offer innovative solutions by designing and projecting in commercial type refrigerators, industrial cooling systems, industrial storage areas, store and market equipment. Founded by a team with more than 20 years of experience, Freeztech serves in many product groups that retailers need. With the concept of turnkey projects, Freeztech presents you closely following the effects of the rapid change in the world and in Turkey on the market and restaurant sector.

• www.freezetechtrade.com

OUR AREAS OF ACTIVITY

1)SUPERMARKET REFRIGERATION EQUIPMENT

2)COOLİNG SYSTEMS

3)COLD ROOM

4) SUPERMARKET SHELF SYSTEMS


5)HEAVY LOAD SHELVES

AND MORE



SUPERMARKET REFRİGERATİON EQUİPMENT


- 1)<u>Half Height Vertical</u> <u>Cabinets</u>
- 2)<u>Full Length Vertical Type</u> <u>Cooler Cabinet</u>
- 3)<u>Vertical Frozen Glass</u> <u>Door Cabinets</u>
- 4) Service Cabinets
- 5)<u>Plug-in Series</u>



Dairy Products Kühlregal


Packed Meat Paket und

LION V2/110/220-205






<u>8</u> 8




LION V2 MT /110/220-205




LION V2 MT /100/220-205


LION V2/90/220-205

LION V2/75/220-205






LION V2 MT /90/220-205




LION V2 MT /75/220-205



LION V2 FV/110/220-205




LION V2 FV/90/220-205



LION V2 FV/100/220-205

LION V2 FV/75/220-205





Operating Ter	mperatures / Betriebs	temperaturen	Ambient Conditions
DP	MT	FV	Umgebungsbedingungen
M2	M1	H1	25°C / 60% RH
(-1/+7°C)	(-1/+5°C)	(+1/+10°C)	(EN ISO 23953-2)

Ava	ilable Mod	ules / Ver	fügbare Mo	dule		
Length/Länge (mm)	1250	1875	2500	3750	Gondola / Head	
Side panel/ Seitenabdeckung (mm)	40	40	40	40	40	-
1						
<u> </u>						







Operating Temperatures	s / Betriebstemperaturen	Ambient Conditions
DP	MT	Umgebungsbedingungen
M2	M1	25°C / 60% RH
(-1/+7°C)	(-1/+5°C)	(EN ISO 23953-2)

Ava	ilable Mod	ules / Verf	ügbare Mo	dule	
Length/Länge (mm)	1250	1875	2500	3750	Gondola / Head
Side panel/ Seitenabdeckung (mm)	40	40	40	40	60

Length (mm) Länge (mm)	2D 1562	les / Verfügbare I 3D 2343	4D 3124	5D 3905
Side panel (mm) eitenabdeckung (mm)	50	50	50	50
Operating Temp Betriebstempe		U	Ambient Conditi Imgebungsbeding	
L1 (-15/-18°C) - L2 (-12/-18°C)		25°C	/ 60% RH (EN IS	0 23953-2)





	A	vailable Mo	dules / Ve	rfügbare M	odule	
Length (mm) Länge (mm)	937	1250	1875	2500	3750	Corner Modules Köşe Modüller
Side panel (mm) Seitenabdeck- ung (mm)	40	40	40	40	40	40
	ing Tempe bstempera				Ambient Co gebungsbe	nditions dingungen
M1(-1/+5	5°C) - M2	(-1/+7°C)		25°C/	60% RH (El	N ISO 23953-2)






	Availa	ble Modules /	Verfügbare Mod	ule	
Length (mm) Länge (mm)	1875	2500	3750	2000 HD	1500 HD
Side panel (mm) Seitenabdeck- ung (mm)	60	60	60	60	60
Operat	ing Temperatur	es	Am	bient Condition	s

Betriebstemperaturen	Ambient Conditions Umgebungsbedingungen
L1 (-15/-18°C) - L2 (-12/-18°C)	25°C / 60% RH (EN ISO 23953-2)



Length (mm) Länge (mm)	1050	
Operating Temperatures Betriebstemperaturen	Ambient Conditions Umgebungsbedingungen	
M1 (-1/+5°C) - M2 (-1/+7°C)	25°C / 60% RH (EN ISO 23953-2)	-







Meat, milk, fruits and vegetables, bakery products, various frozen products, all kinds of food products like ice cream can be stored under the best Conditions and for the longest time possible in our cold storage rooms that are constituted with locked sandwich panels, which have been prepared with 42 kg/m³ density polyurethane. Our cold storage rooms, which could also be produced with glass doors, depending on your request could be used inside of the store for the purpose of both storing and for displaying.

• AISI 304, PVC coating or powder coated sheet metals can be used on internal and external surfaces of panels, depending on your request.

• Our panels can be produced in thicknesses of 80 mm, 100 mm, 120 mm, 160 mm and in 200 mm.


• In our cold storage rooms, which could also be set up with Atmospheric Control System depending on the requirements for large fruit and vegetable storage, fruits and vegetable can be stored under the most appropriate Conditions with the use of this system.

• While the corner panel, which can be manufactured as single piece, provides ease of assembly, it would also provide efficiency for the consumption of the energy at the same time as it provides much better insulation for your cold storage rooms.

• There are options of swing, sliding, monorail, sectional, flip-flap, fast passage and atmospheric controlled doors available depending on the requirements.



Cold Room Doors / Soğuk Oda Kapıları



Modular Cold Room / Modüler Soğuk Oda



ce cream can be stored under the best Conditions and f

ad under the most appropriate Conditions with the use of this

better insulation for your cold str f the energy at the same

here are options of swing, sliding, monorail, sectional, flip-flap, fast pr



Modular Cold Room / Moduler Soğuk Od

Application Types

- Split-Type Refrigeration Units
- Open Type Condensing Units
- Mono Block Refrigeration Units
- Twin Central Refrigaration Systems
- Chiller Units
- Tandem Cooling Systems

Options

- İnvertor Application
- Electronic fan speed control system
- Control from one center by connecting to central automation systems
- Co2 Cooling System
- Heat Exchanger Application
- Heat recovery Applic



Advantages

• In models with a cabin, body of the device is covered with electrostatic powder paint resistant to outer Conditions and has decorative appearance.

- Low cost initial investment.
- High refrigeration performance, wide range of capacity and Permanency of refrigeration.
- 30-35 % energy saving.
- Minimum space occupation.
- Easy installation, maintenance and service.
- Easy programming to requested values.
- Control from one cente by connecting to central automation systems.

CHILLER UNITS

These are the units designed to meet process water-cooling needs of numerous sectors, such as air conditioning, plastics, packing, chemistry, pharmaceuticals, and food. Cold-water units

can be manufactured with cold-water output temperature ranging from +2 °C to +10 °C, according to request. The system is designed with suitable capacity depending on need and load and made up of 1 to 4 semi-hermetic compressors. The elements of a cooling group are optimally located and designed to have the minimum sizes. Operation of compressor and condenser fans is carried out by a microprocessor according to data received from sensors depending on capacity. Upon request, the system operation can be observed and simple interference can be carried out from any remote center by means of connection to control panel through a data line. Power feeding and control panel are located on the unit and all connections are fi nished at the factory.

General Equipments


All types are supplied with the following equipment.

- Semi-hermetic or hermetic compressors.
- Oil separator, oil collector, oil pressure control valve, low and high pressure control automat, on the basis of one per a system.
- Discharge suction line vibration receivers, low and high pressure control automats, and oil level regulators in all compressors.
- Refrigeration liquid collector.
- Humidity receiver fi lters on liquid and return lines.
- Horizontal type liquid accumulator.
- Check valve and ball valves.



Warehouse Shelf Systems

Depo Raf Sistemleri Warehouse Rack Systems





Warehouse Shelf Systems









• www.freezetechtrade.com
















Market Raf Sistemleri Market Shelf Systems













Market Raf S











Kasa Altı Without Belt





Yaprak Turnike Seti Leaf Turnstile Set

0 0



İkili Ekmek Dolabı Tekli Ekmek Dolabı Double Bread Cupboard Single Bread Cupboard












APPLICATION PICTURES




















APPLICATION PICTURES


















reezetech \supset



FREEZETECH İÇ VE DIŞ TİCARET LİMİTED ŞİRKETİ Adres:

• BEYLİKDÜZÜ / İSTANBUL

iletisim:

- +90 549 829 00 17
- <u>hakan@freezetechtrade.com</u>

